

F4 1000 Senna	
ENGINE	
Type	Four cylinder, 4 stroke, 16 valve
Timing system	"D.O.H.C", radial valve
Total displacement	60.8 cu. in.
Compression ratio	13:1
Starting	Electric
Bore x stroke	3.0 in. x 2.2 in.
Max. horse power - r.p.m. (at the crankshaft)	128 Kw (174 HP) at 11900 - Lim. 13000 r.p.m.
Max. torque - r.p.m.	111 Nm (11.3 Kgm) at 10000 r.p.m.
Cooling system	Liquid cooled, water-oil heat exchanger
Engine management system	"Weber Marelli" 5SM ignition - injection integrated system; induction discharge electronic ignition, "Multipoint" electronic injection
Clutch	Wet, multi - disc
Gear Box	Cassette gearbox; six speed, constant mesh
Primary drive	50/79
Gear ratio	
First gear: Speed*	13/38 78.5 mph at 13000 r.p.m.
Second gear: Speed*	16/34 108.1 mph at 13000 r.p.m.
Third gear: Speed*	18/32 129.2 mph at 13000 r.p.m.
Fourth gear: Speed*	20/30 153.1 mph at 13000 r.p.m.
Fifth gear: Speed*	22/29 174.2 mph at 13000 r.p.m.
Sixth gear: Speed*	21/25 187.0 mph at 13000 r.p.m.
Final velocity ratio	15x40
ELECTRICAL EQUIPMENT	
Voltage	12V
Alternator	650 W at 5000 r.p.m.
Battery	12V - 9 Ah
DIMENSIONS AND WEIGHT	
Wheelbase	55.40 in.
Overall length	79.01 in.
Overall width	26.97 in.
Saddle height	31.87 in.
Min. ground clearance	5.12 in.
Trail	4.08 in.
Dry weight	418.8 lb
Fuel tank capacity	4.6 Brit. gal. (reserve fuel: 0.88 Brit. gal.)
PERFORMANCE	
Maximum speed*	187.0 mph
FRAME	
Type	CrMo Steel tubular trellis (TIG welded)
Rear swing arm pivot plates: material	Aluminium alloy
FRONT SUSPENSION	
Type	"UPSIDE - DOWN" telescopic hydraulic fork with rebound-compression damping and spring preload adjustment
Rod dia.	1.97 in. with Titanium Nitride anti-friction treatment
Travel on leg axis	5.07 in.
REAR SUSPENSION	
Type	Progressive, F.I-derived single shock absorber with rebound and compression (High speed / Low speed) damping and spring preload
Single sided swing arm: materiale	Aluminium alloy
Wheel travel	4.72 in.
BRAKE	
Front brake	Double floating disc (Ø 12.6 in.) with steel braking band and aluminum flange
Front brake caliper	Radial-type with 4 pistons (Ø 1.34 in)
Rear brake	Single steel disc (Ø 8.27 in.)
Rear brake caliper	With 4 pistons (Ø 1.00 in.)
RIM	
Front: Material / size	Forged aluminium alloy 3,50 " x 17 "
Rear: Material / size	Forged aluminium alloy 6,00 " x 17 "
TYRES	
Front	120/70 - ZR 17 (58 W)
Rear	190/55 - ZR 17 (75 W)
FAIRING	
Material	Thermoplastic and carbon fiber

* = Top speed attained on closed course.

MV Agusta Motorcycles is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.